

Superior surface-mounted ceiling light with the latest COB-led chip with excellent light and good uniformity. It offers a wide choice of beam angles 24°/36°/45°/60° for optional. The Aluminium AL6063 profile provides excellent thermal dissipation. Isolated driver solution both in dimmable and non-dimmable versions to achieve optimum performance



Application

Office

Transportation

Warehouse

Commercial


Healthcare

Hospitality

PDL-S				
System Power	10W	15W	25W	30W
Lumen	890lm	1500lm	3070lm	3500lm
CRI	>80			
System Efficacy	Up to 116lm/W			
Housing Material	Aluminium Die-casting			
Input Voltage	220-240V 50/60Hz			
Beam Angle	60°			
Glare (UGR)	N/A			
CCT	2700K / 3000K / 4000K / 5000K			
SDCM	<4			
Protection	IP54			
Driver	ON-OFF (DALI OPTIONAL)			
Lifetime	50,000Hrs			
Installation	Surface-Mounted			
Dimension	Ø90x100	Ø90x100	Ø120x110	Ø160x120
Warranty	5-YEARS			

CODE	WATTAGE (W)	LUMEN (lm)	CCT (K)	BEAM ANGLE	DIMENSION (mm)
PDL-S LED08 10W 2700K D90 PSU IP54 S	10	890	2700	60°	Ø90x100
PDL-S LED08 10W 3000K D90 PSU IP54 S	10	890	3000	60°	Ø90x100
PDL-S LED08 10W 4000K D90 PSU IP54 S	10	890	4000	60°	Ø90x100
PDL-S LED08 10W 5000K D90 PSU IP54 S	10	890	5000	60°	Ø90x100
PDL-S LED16 15W 2700K D90 PSU IP54 S	15	1240	2700	60°	Ø90x100
PDL-S LED16 15W 3000K D90 PSU IP54 S	15	1360	3000	60°	Ø90x100
PDL-S LED16 15W 4000K D90 PSU IP54 S	15	1470	4000	60°	Ø90x100
PDL-S LED16 15W 5000K D90 PSU IP54 S	15	1470	5000	60°	Ø90x100
PDL-S LED30 25W 2700K D120 PSU IP54 S	25	3070	2700	60°	Ø120x110
PDL-S LED30 25W 3000K D120 PSU IP54 S	25	3070	3000	60°	Ø120x110
PDL-S LED30 25W 4000K D120 PSU IP54 S	25	3070	4000	60°	Ø120x110
PDL-S LED30 25W 5000K D120 PSU IP54 S	25	3070	5000	60°	Ø120x110
PDL-S LED35 30W 2700K D160 PSU IP54 S	30	3500	2700	60°	Ø160x120
PDL-S LED35 30W 3000K D160 PSU IP54 S	30	3500	3000	60°	Ø160x120
PDL-S LED35 30W 4000K D160 PSU IP54 S	30	3500	4000	60°	Ø160x120
PDL-S LED35 30W 5000K D160 PSU IP54 S	30	3500	5000	60°	Ø160x120

Dimension A x B (mm)



10W	15W	25W	30W
Ø90x100	Ø90x100	Ø120x110	Ø160x120

Note:
Housing with Black RAL9005 is optional. Code (BK) to be added
Ordering Example: PDL-S LED35 30W 3000K D160 PSU IP54 (BK) S

All models option with emergency power pack by adding “EL” to the model description.
Example: PDL-S LED35 30W 3000K D160 PSU IP54 S EL