

Linear batten luminaire is designed as a direct replacement for conventional fluorescent T8 tubes. This luminaire can be easily mounted directly to the ceiling, walls or suspended by chains or conduits. PBBL2 offers the best optimum lighting levels with switchable output power and colour temperatures to suit all applications. Ease of maintenance with torsion spring removable cover design. Best saving with efficient energy level.



PBBL2		
System Power	10W20W	20W/40W
Lumen	1300lm/2620lm	2700lm/5250lm
CRI	>80	
System Efficacy	> 130lm/W	
Housing Material	Formed In White Powder Coated Steel	
Diffuser	Polycarbonate Frosted Diffuser, PC	
Input Voltage	220-240V 50/60Hz	
CCT	3000K / 4000K 5700K (Selectable)	
SDCM	4	
Protection	IP20	
Driver	Dual wattage	
Lifetime	50,000Hrs	
Installation	Surface-Mounted / Pendant	
Dimension	L590 x W65 x H65	L1150 x W65 x H65
Warranty	3-years	

Application



Office



Transportation



Warehouse



Commercial



Healthcare



Hospitality



Transportation



Outdoor
Parking Lot

CODE	WATTAGE (W)	LUMEN (lm)	CCT (K)	DIMENSION mm
PBBL2 10/20W 3CCT/L600	10/20	1300/2620	3000K / 4000K 5700K	L590 x W65 x H65
PBBL2 20/40W 3CCT/L1200	20/40	2700/5250	3000K / 4000K 5700K	L1150 x W65 x H65

Dimension

