

The Streetlight PSL Series is ideal for new and renovating existing installations, this affordable range of lighting set to meet customers’ requirements, including high lumen efficacy for energy saving and sustainability. High-quality light with significant energy savings and reduced maintenance.



Application

Commercial

Healthcare

Industrial

Transportation

Outdoor Parking Lot

Warehouse

PFL			
System Wattage	70W	120W	180W
System Lumen	10,600lm	18,000lm	27,000lm
System Efficacy	> 150lm/W		
CRI	➤ 70		
CCT	3000K / 4000K / 5700k (optional)		
SDCM	5		
Input Voltage	220-240V 50/60Hz		
Power Factor	0.9		
Material	Die-Casting Aluminium Body + Tempered Glass		
System Ready	NEMA socket		
Surge Protection	20kV / 20kA		
IP rating	IP66 / IK09		
Lifetime	100,000 L70 (Hrs)		
Warranty	5-years		

CODE	WATTAGE (W)	LUMEN (lm)	CCT (K)	IP Rating	DIMENSION mm
PSL-70W-840-IP66	70	10,600	4000	IP66	562×250×120
PSL-70W-830-IP66	70	10,600	3000	IP66	562×250×120
PSL-120W-840-IP66	120	18,000	4000	IP66	562×250×120
PSL-120W-830-IP66	120	18,000	3000	IP66	562×250×120
PSL-180W-840-IP66	180	27,000	4000	IP66	722×345×122
PSL-180W-830-IP66	180	27,000	3000	IP66	722×345×122

Dimension

